



Name: Joey Micro6 (+ access port)

Description: Wall mounted AV Control unit, One screen, Six buttons, Customisable, Dealer printed button inlay, tactile buttons with LED's.



A new concept in inexpensive, flexible control systems, Joey Micro6 is a 6 button fully programmable control system that will fit in a standard single gang wallbox. You can create button actions and controls using the same simple authoring software as the rest of the Joey range.

Joey Micro6 will save you money by managing your equipment. Joey Micro6 is smart enough to know when a room is empty and will shut the room down. Especially important where projectors are installed. The Joey Micro does this by tracking time, key presses and room movement.

To customise a Joey Micro6 to suit your application, you design your own layout in landscape or portrait orientation using the simple drag and drop style Joey authoring program. Print the result on a colour printer onto high res paper cut it out and install it under the high gloss clip-on Perspex cover.

Joey Micro6 can directly control your equipment via Infra Red and RS232.

This allows Joey Micro to be a complete control solution, with far more functionality than you might assume from just 6 buttons, because they are context sensitive. LEDs on each button can be programmed to indicate the mode your system is in.

For more demanding applications, Joey Micro6 also directly interfaces to all processors in the CommBox range with full feedback support and will now control the Multi Media Port directly.

Enclosure	Standard single-gang HPM wallplate
Power Supply	12v DC at 10mA (typ.) from IRBus or plugpack
Dimensions	110mm(H) x 67mm(W) x 10mm(D)
Weight	74g
Software	Joey Authoring Program
Connectivity	Connects to Access Port Via single Cat5
Programming port (3.5mm Jack)	X 1
IR Bus Phoenix Connector	X 1
Compatibility	All IR formats supported by TCS. RS232 from 300 to 38400 baud. IRBus
Cut Out Dimensions	As standard single gang wall box
Depth above mounting plane	12mm approx
Dimensions Access Port	110mm(H) x 67mm(W) x 25mm(D) (same as standard single gang wallplate)
Number of programmable keys	6 per "virtual screen"
Number of virtual screens	100 to 300 depending on application
E2 memory	32 kb
Number of loadable codesets	125